

# SECURICLAD

## FIRE RATINGS (SR4 RATED PANEL)

PRODUCT NAME	SPECIFICATION THICKNESS (mm)	MAX UNSUPPORTED SPAN (m)	WALL PANEL ORIENTATION (H/V) (NOTE 1)	FIRE RESISTANCE (min) INTEGRITY / INSULATION	GRADE	CORE MATERIAL	LPCB REF NO.
SECURICLAD SR4 (WALL PANEL)	100	7.5	V	30 / 30	FR30	MINERAL FIBRE	142A/09
	100	7.5	V	60 / 60	FR60	MINERAL FIBRE	
	100	4.0	V	90 / 90	FR90	MINERAL FIBRE	
	100	4.0	V	120 / 90	FR90	MINERAL FIBRE	
	100	4.0	V	180 / 90	FR90	MINERAL FIBRE	
	100	4.0	V	240 / 90	FR90	MINERAL FIBRE	
SECURICLAD SR4 (CEILING PANEL)	100	7.5	-	30 / 30	FR30	MINERAL FIBRE	142A/10
	100	4.1	-	60 / 60	FR60	MINERAL FIBRE	

Note 1: Wall panel orientation, Horizontal or Vertical (H/V) relates to the long joint orientation.

CREATING SECURE ENVIRONMENTS



Tel: +44 (0)191 258 5052 | Email: [sales@securiclad.co.uk](mailto:sales@securiclad.co.uk) | Visit: [www.securiclad.co.uk](http://www.securiclad.co.uk)